

REMARKS

The claims have been amended in the attached Preliminary Amendment to place the application in proper U.S. format and to conform with proper grammatical and idiomatic English. None of the amendments herein are made for reasons related to patentability. No new matter has been added.


In the event the U.S. Patent and Trademark Office determines that an extension and/or other relief is required, applicant petitions for any required relief including extensions of time and authorizes the Commissioner to charge the cost of such petitions and/or other fees due in connection with the filing of this document to Deposit Account No. 03-1952 referencing Attorney Docket No. 449122077800.

Dated: July 27, 2005

Respectfully submitted,

By

Jill E. DeMello



Registration No.: 42,477
MORRISON & FOERSTER LLP
1650 Tysons Boulevard, Suite 300
McLean, Virginia 22102
(703) 760-7718 - Telephone
(703) 760-7777 - Facsimile

Description

**METHOD FOR DAMPING PRESSURE OSCILLATIONS IN THE A MEASURING
SIGNAL OF A LAMBDA PROBE**

CLAIM FOR PRIORITY

TECHNICAL FIELD OF THE INVENTION

The invention relates to a method for damping pressure oscil-
10 lations in a measuring signal of a lambda probe, and in par-
ticular, to obtaining a correctively adjusted output signal
from the measuring signal, having a periodic pressure depend-
ence, of a lambda probe located in the exhaust of an internal
combustion engine, ~~whereby said measuring signal is sampled~~
15 ~~in a time-slot pattern and averaged through totaling over a~~
~~specified summation period, said period corresponding to the~~
~~period of oscillation, dependent on engine speed, of pressure~~
~~pulsations of the exhaust.~~

BACKGROUND OF THE INVENTION

~~A method of this type is already known from DE 37 43 315 A1-~~
~~discloses oxygen~~ Oxygen sensors mounted in ~~the an~~ exhaust
pipe ~~are~~ used to continuously determine the air/fuel ratio
with a high response rate in both the "lean" - lambda greater
25 than one - and the "rich" - lambda less than one - mixture
range. These, what are termed continuous or linear lambda
probes, operate according to the two-cell limit-current probe
principle and can be used as pre-cat probes for injection
controlling (lambda controlling), but especially for control-
30 ling lean-burn engines, for example Otto engines having di-
rect fuel injection.

The measuring signal of a lambda probe depends on a plurality
of variables, ~~particularly on~~ including the oxygen concentra-
35 tion to be determined in the exhaust ~~but also on~~ and the tem-
perature of the ceramic and the counter-pressure of the ex-
haust, with the degree of ~~the~~ pressure dependence of the

measuring signal being defined by the design of the probe. A distinction must be made where ~~said the~~ pressure dependence is concerned between a static and a dynamic pressure dependence. Typical variations in the dynamic pressure dependence of the measuring signal are within the significant range in the case of continuous lambda probes and hence are an order of magnitude higher than for what are termed binary lambda probes. The following concerns the damping or, as the case may be, elimination of periodic pressure-related influencing factors, especially in connection with continuous lambda probes.

Pressure pulsations in the exhaust system are due partly to the abrupt rise in the positive pressure curve triggered by ~~the a~~ a pressure surge produced when discharge valves of a cylinder are opened. A waveform pressure curve is produced by reflections or, as the case may be, overlapping of the exhaust oscillation in the exhaust system until another pressure surge occurs ~~accompanying upon~~ the cylinder's next ejection stroke. An internal combustion engine operated by the four-stroke method therefore produces a dynamic exhaust-pressure curve having a periodicity of 720-°KW referred to the crankshaft, which is to say dependent on engine speed. The possibility of hardware-based filtering is limited, as because the frequency of the pressure-dependent interference within the lambda signal depends on the internal combustion engine's speed, and the central control device of the internal combustion engine must also continue being remain suitable for measuring rapid processes (lambda controlling on a cylinder-selective basis, for instance). ~~Owing to~~ Based on the above-described characteristic periodicity of the processes, signal filtering requires averaging over a specific crank-angle range of the internal combustion engine, for example, in the case of a four-cylinder four-stroke internal combustion engine having a single-flow exhaust system, $720-^{\circ}\text{KW}/4 = 180-^{\circ}\text{KW}$.

The generic method accordingly proposes an integration period or, ~~as the case may be,~~ summation period corresponding to the engine speed dependent period of oscillation of the pressure curve, ~~in other words~~ which is 180°KW in the cited example
5 | above. Above-cited DE 37 43 315 A1 ~~also~~ mentions the possibility of providing separate summation equipment to relieve the vehicle's microcomputer of the special function of signal filtering. The following problems are ~~in fact~~ involved:

10 | The known method for averaging obviously requires a relatively large amount of memory area to be reserved for the individual measurements of the lambda probe signal which are sampled in, for example, a 1-ms time-slot pattern and buffered in a ring memory. For further processing of the lambda
15 | probe signal, averaging would then be initiated at each instant at which a filtered output signal is required (say
e.g., every 10 ms) by totaling a number N1 of buffered individual values and dividing the result by N1. For the given
20 | sampling time-slot pattern the number N1 would exactly correspond to the period of oscillation of the pressure curve.
With this procedure, for a four-cylinder internal combustion engine, 50 individual values would ~~at any rate~~ have to be
stored simultaneously in the ~~ring memory in the case of~~ for,
~~say e.g.,~~ 600 revolutions; for a 6-cylinder two-bank system a
25 | total of 67*2=134 individual values would ~~accordingly~~ have to be stored. Averaging would furthermore always, which is to
say at each update time, have to be carried out across the entire number of N1 measurements for the period to be considered so that, especially in the case of slow engine speeds,
30 | the summation value would be formed several times over certain sections of the ~~ring~~ memory.

SUMMARY OF THE INVENTION

35 | The invention relates to a method for obtaining a
correctively adjusted output signal from the measuring signal, having a periodic pressure dependence, of a lambda probe located
in the exhaust of an internal combustion engine, whereby said

measuring signal is sampled in a time-slot pattern and averaged through totaling over a specified summation period, the period corresponding to the period of oscillation, dependent on engine speed, of pressure pulsations of the exhaust.

~~The object of the invention is to describe a method of the type mentioned at the beginning which is improved particularly in terms of memory space resources and computing time requirements.~~

~~Said object is achieved according to the invention by means of a method according to claim 1.~~

According to one embodiment of the invention, the ~~procedure~~ method for signal evaluation is for ~~the~~ continuously--sampled individual values of the measuring signal to be buffered in a memory area of a memory of a control device for the internal combustion engine and for averaging that includes a number N1, corresponding to the summation period, of individual values sampled in the time-slot pattern to be initiated by the control device at each instant at which an updated probe output signal is required. ~~According to the invention, however,~~ These steps are performed in such a way that totaling is carried out across the N1 individual values block-by-block and starts before the update time so that the block values already formed continuously block-by-block up to the update time and buffered, instead of the respective individual values, are used for calculating an average.

The signal conditioning method according to the invention is therefore geared in particular to a favorable block algorithm according to the formula

$$VLS = \frac{1}{N1} \left[\sum_{i=1}^{M1} VLS_1ms + \sum_{i=M1+1}^{2*M1} VLS_1ms + \dots + \sum_{i=N*M1+1}^{N1} VLS_1ms \right]$$

which ~~paves the way for~~ facilitates advantageous memory configuring or; as the case may be, memory organization. In the above formula, VLS signifies the average, currently requiring to be calculated, of the lambda probe voltage signal, VLS_lms signifies ~~in each case~~ a single non-linearized value of the lambda signal sampled in, for instance, a 1-ms time-slot pattern, N1 signifies the number, dependent on engine speed, of individual values employed according to the period of oscillation for averaging, N signifies a whole number, and M1 signifies the block length, which is to say the number of individual values contained in a block.

The summation values already continuously formed block-by-block over M1 measuring signals and the remainder of the N1-
(N*M1) measurements are accordingly used for calculating an average VLS. The storage requirements can thereby be reduced to such an extent that only (N+M1) block values or, ~~as the case may be,~~ individual values have to be buffered. There is also a reduction in computing requirements. The maximum possible engine speed and the updating rate of the averaged measurement must be taken into consideration in determining the number M1. The relationships improved according to the invention can be made clear using ~~as an~~, for example, the recording of measurements over an extended period of time, in this case 1 s, with updating being performed in a 10-ms time-slot pattern and with averaging over N1=30 measurements (M1=10):

Previously : 100*30 summations + 100 divisions
Invention : 100*10 summat. + 100*3 summat. + 100 divisions
Prev. storage requirements—: 50 values (~~as~~ at slow engine speeds it is possible for N1 > 30)
Storage requirements, invention—: 10 (indiv.) values + 4 values

In one embodiment, ~~t~~The invention is directed ~~at to~~ segment-synchronous averaging. This means that, for totaling purposes, it should ~~at any update time basically be possible,~~ at any update time, to "look back" immediately and precisely over the N_1 last sampled individual values forming the segment currently being averaged of the ~~continuously~~ continuously-sampled individual values.

So that this can be realized in the context of block-by-block totaling, according to the invention, it is advantageous to perform the following partial synchronizing ~~in a first step:~~

Block-by-block totaling is carried out over ~~in each case~~ M_1 ~~sequentially~~ sequentially-sampled and buffered individual values (M_1 block) and is performed in a block time-slot pattern corresponding to M_1 times the sampling time-slot pattern (sampling rate), as a result of which the updating rate can be synchronized with the M_1 block time-slot pattern. In the event that the segment length is an integer multiple of the block length, which is to say if $N_1 = N \cdot M_1$, segment-synchronous averaging can then be realized simply by using the $N - N -$ buffered block values for calculating. It is, however, also possible to total the $N - 1$ block values and all M_1 individual values in the "last" M_1 block ending at the update time.

In the case of a segment length N_1 differing from the multiple of the block length, for averaging that is as segment-synchronous as possible, it is necessary in a second step to ~~carry out~~ perform further partial steps amounting to taking into consideration either at the end or at the beginning of the summation period only the required part of the relevant M_1 block and not all individual values, at least not for current averaging, in order to exactly include N_1 individual values in averaging despite the incommensurability prevailing in such cases between block length M_1 and segment length N_1 .

According to a ~~first~~one embodiment, it is advantageous in these cases, where the number $N1$ does not correspond to a multiple N of $M1$, to include the first $N1-N*M1$ individual values in the last sampled $M1$ block that extend beyond a maximum multiple $N*M1$ individually in a current averaging, with the remaining individual values in ~~said the~~ $M1$ block being left out of consideration here and ~~only~~ included in the averaging following the current averaging in the form of a block value to be formed for this entire $M1$ block and buffered. In this embodiment, a defined number (1 to 9, for example, in the case of an $M1=10$ block) of individual values occurring immediately before the update time that are not to be processed in the current summation period will accordingly initially be left out of consideration. A "dead time," amounting, in the example given, to ~~1 to 9~~ times the individual value sampling interval (sampling rate), ~~must~~ should be accepted, ~~it needs to be said,~~ in the case of this ~~first~~ embodiment in terms of the average's actual currency at the update time.

In a ~~particularly advantageous alternative~~ second embodiment, certain remaining, currently not required, individual values temporally preceding the current summation period in an earliest $M1$ block to be used for the current averaging are left out of consideration. Specifically, in ~~the cases under consideration~~ where the number $N1$ does not correspond to a multiple N of $M1$, each $M1$ block is split into two partial blocks $B1$ and $B2$, with the partial block $B2$ ~~containing~~ including the last $N1-N*M1$ individual values in the respective $M1$ block that extend beyond a maximum multiple $N*M1$ and with the partial block $B1$ ~~containing~~ including the remaining first $M1-(N1-N*M1)$ individual values in the $M1$ block. The two respective partial blocks $B1$ and $B2$ are furthermore totaled block-by-block in a block time-slot pattern into partial block values MW_B1 and MW_B2 , which are buffered in place of the respective individual values. Finally, the two partial block values in the N last processed $M1$ blocks and the partial

block value MW_B2 of the M1 block processed immediately before the N last M1 blocks are then used for current averaging. A dead time is thereby avoided and averaging actually takes place over the N1 individual values immediately preceding the update time.

The advantages of a reduction in memory space requirements facilitated by the invention can be realized in particular by operating the memory area in the ring memory mode.

The method is particularly suitable in conjunction with evaluating the measuring signal of a lambda probe which has a continuous characteristic curve of ~~said the~~ measuring signal and which is located upstream of a catalytic converter of the internal combustion engine.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is explained in more detail below with reference to exemplary embodiments and the figures in the drawings, in which:

Figure 1 ~~is a schematic of~~ shows an internal combustion engine having a lambda probe whose signal is to be conditioned.

Figure 2 is a chart showing ~~for~~ different speeds of the internal combustion engine ~~the~~ and time dependence of the signal being conditioned, ~~and~~.

Figure 3 is an organization chart of ~~memory steps or, as the case may be, computing steps~~ shown symbolically in three levels for processing individual lambda signal values according to an embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 shows, in block diagram form, an ~~arrangement in which application of the method according to the invention is applied~~. The only components shown ~~here~~ are those necessary

for understanding the invention. _An air/fuel mixture is routed to the internal combustion engine 1 through an intake channel 2. _An air-mass meter (not shown ~~here~~), ~~for example~~, can also be located in the intake channel 2. _The internal combustion engine 1 is connected on the output side to an exhaust channel 3. _Provided in the exhaust channel 3 ~~viewed in the direction of exhaust flow~~ is a first lambda probe 4, a three-way catalytic converter 5 serving to convert harmful exhaust constituents, and a second lambda probe 6. _The fuel/air ratio in the exhaust ahead of the catalytic converter 5 is determined with the aid of the first lambda probe 4 (control probe) having a continuous characteristic curve. The second lambda probe 6 (monitor probe) serves, inter alia, to check the catalytic converter 5 and typically has a binary characteristic curve. _Located at a suitable position on the internal combustion engine 1 is a speed sensor 7 which serves to register the speed of the internal combustion engine 1 and whose signal is routed to a central control device 8 over an associated connecting lead.

To control and regulate the internal combustion engine 1 the control device 8 can be connected via a data and control lead 9, shown only schematically, to ~~further~~ additional sensors and actuators. _The control device 8 which, inter alia, controls the injection process has, ~~in a known manner~~, a microcomputer 10, corresponding interfaces for signal conditioning circuits, and an input/output unit. _The microcomputer 10 includes a central processing unit (CPU) that performs the arithmetic and logical operations applying the supplied data. The programs and reference data required for this are supplied by a read-only memory (ROM). _A random access memory (RAM) 11 serves, inter alia, to store the data supplied by the sensors until it is called up by the microcomputer 10 or replaced, which is to say overwritten, by more current data. The method according to the invention serves essentially to spare the resources of ~~said the~~ memory 11, which are burdened by the necessary buffering in an area of ~~said the~~ memory 11

of values which are associated with the corrective adjustment of the pressure dependence of the measuring signal of the lambda probe 4.

5 The top part of Figure 2 shows a periodically time-dependent voltage signal UM representing the unfiltered measuring signal of the lambda probe 4. The thin vertical lines indicate the pattern of the updating rate T of the output signal, with averaging over a period of oscillation TP, dependent on engine speed, of pressure pulsations of the exhaust taking place every 10 ms in the example shown (four-cylinder engine having a single-flow exhaust system). ~~Said~~The updating rate T=10 ms is synchronized with the M1 block time-slot pattern, which is in turn based on the 1-ms time-slot pattern selected here for sampling individual values. Each M1 block therefore ~~contains~~includes 10 individual values in the example given. The filtered output signal, calculated in each case at the update times t_n or, as the case may be, t_n' , is represented by the voltage values UA indicated by dots in Figure 2. As can be expected for a properly controlled operating state, the averaged lambda output signal therefore exhibits a constancy across the different engine-speed ranges D1 or, as the case may be, D2, marked by the thick vertical lines, of the internal combustion engine 1.

25 As averaging has to take place precisely over one period of oscillation TP of the pressure pulsations, a length of summation dependent on engine speed, which is to say TP1 for D1 and TP2 for D2, is first determined by the control device 8. 30 A defined number of single non-linearized values of the measuring signal corresponds to this summation period, depending on the selected sampling rate of the measuring signal, in this case 1 ms. In the example shown in Figure 2, the left-hand part of the figure shows a range D1 having an increased engine speed (1,666 revolutions/min, for instance) where a summation period of 18 ms is calculated so that, for averaging, it is necessary in each case to total, across a segment

totaling $N1=18$, individual values VLS_{lms} . At each update time t_n , in this case, for instance, at the end, marked by the left-hand thick line, of the engine-speed range D1, it is necessary in each case to total across precisely 18 of the past individual values, as indicated in Figure 2 by means of the 18 short lines and the arrow above them symbolizing the retrospective view adopted for averaging. On the other hand, there is a relatively longer summation period for the area between the two thick vertical lines in Figure 2 owing to the range D2 represented there having a slower engine speed and, in keeping with this, there is a correspondingly greater number $N1$ of individual values to be totaled, in the example shown here ($D2=714$ revolutions) $N1=41$. The segments n' or, ~~as the case may be,~~ $n'-1$ to be observed at the update time t_n , and, immediately preceding this, $t_{n'-1}$, are indicated in the engine-speed range D2 in Figure 2, again ~~by means of~~ using arrows.

According to an embodiment of the invention, the 18, ~~for example,~~ individual values VLS_{lms} in the faster engine-speed range D1 shown, which are to be totaled, are not all stored in the buffer until summation. ~~Rather it is the case that,~~ the first 10 temporarily first sampled individual values in a segment are written successively to the buffer, where applicable, with the individual values in a ($M1=10$) block created during immediately preceding averaging being overwritten, and are then processed block-by-block, ~~which is to say are i.e.,~~ they are totaled into a block value at the end of the relevant ($M1=10$) block time interval. This individual block value representing the filtered information, assembled from 10 individual values, about the average of the measuring signal in the time interval of the given block, is retained in the buffer until the next updating, while the 10 buffered "old" individual values are successively overwritten in the ring memory mode by the 10 individual values in the next ($M1=10$) block.

According to a first embodiment of the invention, in the example ~~selected~~ shown in Figure 2, it is possible (in the D1 range) to proceed in such a way that the first (in this case: single, since $N1=18=1*10+8$, so: $N=1$) block value is buffered, and that in the next block time section the 8 individual values still missing from the segment of the $N1=18$ individual values to be used in total for averaging are initially written one after the other to the positions previously occupied by the old individual values. It is also possible ~~that~~, in keeping with the time-slot pattern, two further individual values are sampled and written, and that due updating of the average is carried out on completion of said "last" block time section in such a way that the individual block value and the individual first 8 individual values in the last created ($M1=10$) block are totaled. In parallel with this, ~~all~~ 10 individual values in the last created ($M1=10$) block are totaled into a block value, used during the next updating, and buffered. In the example given, the "current" average determined at a specific update time t_n is therefore, strictly speaking, already 2 sampling intervals "old", intervals which according to the specified synchronizing have to be waited out.

Figure 3 ~~relates to~~ illustrates a second embodiment of the invention that can be used in cases $N1 \neq N * M1$ as an alternative to the method discussed in connection with Figure 2. A single-flow exhaust system of a four-cylinder engine running at 1,304 revolutions per minute, updating in a 10-ms cycle, a sampling time-slot pattern of 1 ms, a block length $M1$ of 10 individual values, and a summation period of 23 ms, which is to say a segment length $N1=23$, are assumed in the following explanations by way of example.

The top level ("single-value memory") of Figure 3 relates to the sampling or, ~~as the case may be~~, buffering of the, ~~in each case~~, 10 individual values in a block ~~currently~~ to be processed. ~~T~~Shown ~~there is only the last of the four blocks~~

considered ~~in~~ are illustrated in Figure 3 by way of example, with ~~said~~ the last block, as indicated symbolically, having been divided, as were the three blocks processed before it, into a first partial block B1 ~~containing~~ including 7 individual values and a second partial block B2 ~~containing~~ including 3 individual values. Specific dividing in this way is due, in the example being considered, to the fact that, in accordance with $N1=23=2*10+3$, a partial block B2 having 3 individual values is required for further calculation.

The middle level in Figure 3 shows four pairs of partial block values MW_B1 and MW_B2 (the end digit added in the figure relates to origination from one of the four individual value blocks; the lines symbolizing the block values are not to be referred directly to the time axis of the lower level), which were generated one after the other ~~in each case~~ from the corresponding individual value block among the four $M1=10$ individual value blocks and buffered. For example, the first 7 individual values in the first block were totaled into the partial block value MW_B1_1 and buffered when ~~all~~ 10 individual values in this block had been sampled and buffered, while the last 3 individual values in this block were totaled into the partial block value MW_B2_1 and buffered. The ~~no no longer longer~~ longer required associated individual values can then be overwritten by the new individual values in the next, second block. The new individual values are then processed into partial block values MW_B1_2 and MW_B2_2 in a manner analogous to the process for the first block.

~~Only~~ The partial block values buffered according to the middle level are required for calculating the average, the results of which calculation are represented symbolically by the lower level ("measurement output") in Figure 3. As indicated schematically for two update times by ~~means of~~ lines between the middle and lower level, the current average due after, for instance, 30 ms is calculated by totaling the two partial block values arising from the third block immediately

preceding the update time, the two partial block values arising from the second partial block, and the partial block value MW_B2_1 arising from the first block (~~and~~ dividing the result by N1). It is thereby possible, at the respective update time, ~~immediately~~ to look back at the required exact number N1, in this case N1=23, of individual values immediately preceding the update time.

~~It is advantageous if in the case of~~ In a preferred embodiment of the invention, in at least one of the processed M1 blocks, one of the two partial block lengths is also buffered until current averaging.

The use of resources and computing time required by the calculations involved in signal conditioning can, as described, be significantly reduced through block-by-block pre-processing of the individual values of the measuring signal of the lambda probe, the main impact of this being a savings in memory ~~space~~ resources. A factor to be taken into account ~~here~~ is that calculating in a 1-ms time-slot pattern and providing, for example, ~~(around)~~ about 140 memory locations for a two-bank system places heavy demands on the overall resources of an engine control. The advantage according to the invention is therefore ~~brought more to bear in~~ inadvantageous for multi-bank systems.